

# Romi

## Convertible Car Seat


Your model may look different than one shown on cover.

**Rear-Facing: 5-40 lb (2.3-18 kg) and  
19-40 in. (48-101.6 cm)**

**Forward-Facing: 22-40 lb (10.1-18 kg) and  
29-43 in. (73.6-110 cm) and at least 1 year old**

**Read all instructions BEFORE USING this car seat.**

**KEEP INSTRUCTIONS FOR FUTURE USE.**

 Failure to follow the warnings on the labels and in the instruction manual can result in serious injury or death to your child.




4358-8176B 08.22.22




## Welcome to the Maxi-Cosi Family!

Thank you for choosing this car seat, also known as a child restraint!

To help you get started using your child's new car seat, here are the 4 main tasks you'll need to complete.





**Your child's safety is worth the time it will take to read and follow these instructions.**

**Ready? Let's go!**

**Pages 1-4** will introduce you to the parts of the car seat.

**The Back Cover of this Manual and page 66** has our contact information.

If at any point you would like assistance, please feel free to reach out to us.

# Contents

## 1 Getting Started

---

- 1 Parts of Car Seat
- 3 Accessory Use
- 5 Choosing Car Seat Mode

## 7 Rear-Facing Section

---

- 9 Rear-Facing Child Fit
- 11 Rear-Facing Vehicle Install

## 19 Forward-Facing Section

---

- 21 Forward-Facing Child Fit
- 23 Forward-Facing Vehicle Install

## 30 Securing Child in Car Seat

---

## 33 Making Adjustments to Car Seat

---

- 33 Changing Harness Height
- 36 Changing Buckle Position
- 39 Harness System Adjustments for Smaller Infants

## 45 Wash & Care

---

- 45 Removing Seat Pad & Harness System
- 47 Cleaning Parts of Car Seat
- 48 Installing Seat Pad & Harness System

## **51 LATCH & Vehicle Belt Information**

---

- 51 LATCH: Lower Anchor Belt**
- 53 Vehicle Belts**
- 57 Top Tether**

## **58 Safety Information**

---

- 58 Child Restraint Use**
- 59 Vehicle Seating Position**

- 60 Installation in Vehicle**
- 61 Replacement & Expiration**
- 62 Registration & Safety Notices**
- 63 Aircraft Information**

## **64 Warranty**

---

## **66 Replacement Parts List**


---

©2022 Dorel Juvenile Group, Inc. (800) 951-4113 [www.maxicosi.com](http://www.maxicosi.com). Styles and colors may vary. Los estilos y los colores pueden variar. Made in USA from American and imported parts (including seat pad). Hecho en EE.UU. a partir de piezas americanas e importadas (incluyendo la almohadilla del asiento). Distributed by (distribuido por) Dorel Juvenile Group, Inc., 2525 State St., Columbus, IN 47201-7494. Dorel Juvenile Canada, 2233 Argentinia Road, Suite 110, Mississauga, ON L5N 2X7. Importado y Distribuido en Chile por: Comercial e Industrial Silfa S.A. - San Ignacio 0201 / Parque Industrial Portezuelo Quilicura, Santiago Chile. Fono (562) 2339 9000. En Perú por: Comexa S.A. - Los Libertadores 455 - San Isidro, Lima - Perú. Fono (511) 4469014. En Centro América, Caribe y Ecuador por: Best Brands Group S.A. - Av. Balboa, Bay Mall Plaza, Planta Baja, local 9, Panamá. - Fono: (507) 300 2884. En Colombia por: Baby Universe S.A.S. - Vía 40 No. 77-29, Barranquilla, Colombia - Fono: (575) 353 1110 Importador: DJGM, S.A. DE C.V. Gabriel Mancera No. 1041 Col. Del Valle, Benito Juárez C.P. 03100 México, Ciudad de México R.F.C. DJG140305GN9 Tel. (55) 67199202



# Parts of Car Seat




1



Your model may look different than one shown.


\*See pages 3-4 for Accessory Use.

## Harness System



## Accessory Use


3



**Removable Cup Holder**  
(on select models)

For Use in **Rear-Facing Mode** or **Forward-Facing Mode**

The cup holder is top-rack dishwasher safe.



The cup holder can be attached to either side of the car seat.


Pull the pad off the corner of the car seat.


Align the symbol on the cup holder with the symbol on the car seat.

Hook the bottom of the cup holder under the edge of the car seat.

Snap the top of the cup holder over the edge of the car seat.

Replace the pad.






### Head Pillow

(on select models)

#### Only For Use in Rear-Facing Mode

**To remove**, from the back of the head pillow gently pull the fabric tabs out of the shoulder harness slots.

**To attach**, slide the fabric tabs into the shoulder harness slots.



### Harness Covers


(on select models)

#### For Use in Rear-Facing Mode or Forward-Facing Mode

If the harness covers will not allow proper positioning of the chest clip or interfere with getting a tight enough harness fit for a smaller baby, remove them and **DO NOT** use.

Store them until your child is large enough to use the harness covers while maintaining a properly fitting harness.

**To remove**, pull the fastening strips apart and pull the harness covers off of the harness straps.



## Choosing Car Seat Mode

5

### **WARNING:**

Measure your child's weight and height (**DO NOT** guess) before choosing this car seat's mode.

Your child's height, weight, and age determine how the car seat should be placed in the vehicle.

Children vary widely in body size, shape, and temperament—**please consult your doctor before switching between any modes within the limits and fit requirements of the car seat.**

### State Laws

Please be certain to follow your state's laws regarding car seat use.

### American Academy of Pediatrics Recommendations

#### Infants and Toddlers

Should ride in a rear-facing car seat as long as possible, until they reach the highest weight or height allowed by their car seat.

#### Toddlers and Preschoolers

Once they are facing forward, children should use a forward-facing car seat with a harness for as long as possible, until they reach the height and weight limits for their car seats.

#### School-Aged Children

Once they have outgrown their forward facing car seat, children should use a belt-positioning booster seat until the vehicle's lap and shoulder seat belt fits properly. This is often when they have reached at least 4 feet 9 inches in height and are 8 to 12 years old.

#### Older Children

All children younger than 13 years should be restrained in the rear seats of vehicles for optimal protection.



## Rear-Facing Mode

**5-40 lb (2.3-18 kg) and  
19-40 in. (48-101.6 cm)**

**Rear-Facing Section  
PAGE 7**

**Rear-Facing Child Fit  
PAGE 9**

**Rear-Facing Vehicle Install  
PAGE 11**



## Forward-Facing Mode

**22-40 lb (10.1-18 kg) and  
29-43 in. (73.6-110 cm) and  
at least 1 year old**


**Forward-Facing Section  
PAGE 19**

**Forward-Facing Child Fit  
PAGE 21**

**Forward-Facing Vehicle Install  
PAGE 23**

## Rear-Facing Section

7



**5-40 lb (2.3-18 kg) and 19-40 in. (48-101.6 cm)**

Children under 1 year of age **MUST** ride **Rear-Facing**.

**In this car seat, your child can remain **Rear-Facing** until they outgrow any one of the following:**

- **Weight Limit:** 40 lb (18 kg); **OR**
- **Height Limit:** 40 in. (101.6 cm); **OR**
- **Rear-Facing Child Fit** requirements, see page 9.

Before installing the car seat in your vehicle, check your child's fit in the car seat.

This way you won't have to redo the vehicle installation to make adjustments to the car seat.

**Rear-Facing Child Fit: Page 9**

**Rear-Facing Vehicle Install: Page 11**

## **WARNING:**



**NEVER** install a rear-facing child restraint in the front seat of a vehicle equipped with an active frontal airbag.

**DO NOT** use the tether for rear-facing mode. Secure the tether strap hook to its storage attachment.

**DO NOT** use the lower anchor belt along with the vehicle lap or lap/shoulder belt.

**DO NOT** fasten multiple lower anchor connectors or hooks on the same lower anchor bar in the vehicle.

Check the vehicle belt or the lower anchor belt before each use. Use **ONLY** if the belt can be tightened properly and locked securely in place.


Even when unoccupied, this child restraint **MUST** be firmly secured to the vehicle with the lower anchor belt or with the vehicle seat belt.

This child restraint **MUST ALWAYS** face the rear of the vehicle until the child is at least 1 year old and weighs 22 lb (10 kg).

## Rear-Facing Child Fit

9


1



### Fully Loosen Harness Straps

Push down on the harness release lever (through the opening in the pad) while pulling out on the harness straps as shown.


2



### Undo Chest Clip & Buckle

It may be easier to undo the buckle by pressing in towards the top of the button.


3



### Place Child in Car Seat

Your child's bottom and back should be flat against the car seat.


4



### Check Head Position

The top of your child's head **MUST** be at least 1 in. (2.5 cm) **below** the top of the car seat.


5



### Check Harness Strap Position

The harness strap **MUST** be **at or slightly below** the shoulders; never above.

6



### Check Buckle Position

- Use the slot closest to your child.
- The buckle **should not be underneath or behind** your child.

**DO NOT** use the 3rd buckle slot in **Rear-Facing Mode**.

i

To change the harness strap height, see pages 33-35.

To change the buckle position, see page 36-38.

To learn how to check harness tightness, see pages 30-32.

If you cannot achieve a snug harness fit for your child, see pages 39-44.

## Rear-Facing Vehicle Install

11



Before installing the car seat in your vehicle, check to see if you need to adjust the buckle position or harness height for your child. **See page 9 for child fit.**

Once the car seat is installed, you will not be able to adjust the buckle position or the harness strap height.

### Review Vehicle Owner's Manual

Determine what kind of vehicle belts your car has and how to use them to lock a car seat in place **OR** where LATCH: lower anchor seating positions are located in your vehicle.

There are 2 different methods for install.

**Use only one:**



**Vehicle Belt**




**LATCH: Lower Anchor Belt**

**⚠ WARNING:**

**DO NOT** use both the LATCH: lower anchor belt and vehicle belt at the same time to install the car seat.

1



Place Car Seat **Rear-Facing** in Back Seat

2




Check **Rear-Facing Level Line**

The **Rear-Facing Level Line** on the car seat **MUST** be parallel with the ground.

*continued on next page*

3



### Locate **Rear-Facing Belt Path** & Route Vehicle Belt or Lower Anchor Belt Through It

**For the LATCH belt:** You may need to fully lengthen the belt before routing it into the belt path. Squeeze the adjuster button and pull the belt out as shown below.




Connector



Hook

4




### Vehicle Belt or Lower Anchor Belt Goes:


- under the car seat pad; **AND**
- across the car seat; **AND**
- in front of the buckle; **AND**
- out the other **Rear-Facing Belt Path** opening.

**DO NOT twist the belt.**

5



OR




### Buckle Vehicle Belt

If your car has a **switchable retractor**, use it to lock the vehicle belt. Review page 55 of this manual or your vehicle owner's manual.

### Depending on Your Model: Attach Lower Anchor Belt Connectors or Hooks to Vehicle's Lower Anchors As Shown

i




The lower anchor connector should be attached to the vehicle's lower anchor bar with the thicker side at the top as shown.

**DO NOT** twist the belt.



*continued on next page*

i



### Finished Lower Anchor Belt Routing

6




### Tighten Belt

Place your hand in the car seat and firmly push the car seat down and back towards the vehicle seat. Pull the belt towards you and parallel (in line) with the belt path as shown.

**For the LATCH belt or Lap Only Vehicle Belt:** it may be easier to tighten if you route the free end of the belt back into the **Rear-Facing Belt Path**, reach into the **Rear-Facing Belt Path**, and pull the free end of the belt towards you.

7



### Check Belt Tightness

Hold the **Rear-Facing Belt Path** with your non-dominant hand. Push and pull the car seat from side to side.

The car seat should not move more than **1 in.** (2.5 cm).

i

If the car seat moves more than 1 in. (2.5 cm), you can try:

- Pulling the belt tighter; **OR**
- Reinstalling the car seat; **OR**
- Changing to a different seating location; **OR**
- Switching to a different install method (LATCH or vehicle belt).

8




### Secure Child in Car Seat

See pages 30-32.

*continued on next page*

9




### Recheck Rear-Facing Level Line

Redo the installation if the **Rear-Facing Level Line** is not parallel with the ground.

See info box on this page.

i



Only if necessary, you may place a tightly rolled towel(s) or foam pool noodle(s) under the front of the car seat to help make the **Rear-Facing Level Line** parallel with the ground.

Check often to make sure padding is still in place and the belt is tight.

# FINISHED!



## Lap/Shoulder Belt


**Vehicle Belt Install:** Is the vehicle belt locked? See step 5.



## Lap Belt

**LATCH: Lower Anchor Belt Install:** Are the connectors or hooks securely attached to the vehicle's lower anchors? See step 5.

Is the belt tightened enough so that the car seat does not move more than 1 in. (2.5 cm) from side to side? Check the tightness of the install often to make sure it has not loosened. See steps 6 and 7.



## LATCH: Lower Anchor Belt

Is the **Rear-Facing Level Line** parallel with the ground? See steps 2, 9, and info box on page 17.

## Forward-Facing Section

19



**22-40 lb (10.1-18 kg) and 29-43 in. (73.6-110 cm) and at least 1 year old**

Children **MUST** be at least 1 year of age to ride **Forward-Facing**.

**In this car seat, your child can remain harnessed **Forward-Facing** until they outgrow any one of the following:**

- **Weight Limit:** 40 lb (18 kg); **OR**
- **Height Limit:** 43 in. (110 cm); **OR**
- **Forward-Facing Child Fit** requirements, see page 21.

Before installing the car seat in your vehicle, check your child's fit in the car seat.

This way you won't have to redo the vehicle installation to make adjustments to the car seat.

**Forward-Facing Child Fit: Page 21**

**Forward-Facing Vehicle Install: Page 23**

## **WARNING:**

You **MUST ALWAYS** attach, adjust, and secure the tether (top anchorage) strap when installing the car seat in the Forward-Facing Mode with internal harness.

**DO NOT** use the lower anchor belt along with the vehicle lap or lap/shoulder belt.

Check the vehicle belt or the lower anchor belt before each use.

Use **ONLY** if the belt can be tightened properly and locked securely in place.

**DO NOT** fasten multiple lower anchor connectors or hooks on the same lower anchor bar in the vehicle.


Even when unoccupied, this child restraint **MUST** be firmly secured to the vehicle with the lower anchor belt or with the vehicle seat belt.

In this child restraint your child **MUST** be at least 1 year old and weigh 22 lb (10.1 kg) before they sit forward-facing.

## Forward-Facing Child Fit

21


1



### Fully Loosen Harness Straps

Push down on the harness release lever (through the opening in the pad) while pulling out on the harness straps as shown.


2



### Undo Chest Clip & Buckle

It may be easier to undo the buckle by pressing in towards the top of the button.


3



### Place Child in Car Seat

Your child's bottom and back should be flat against the car seat.


4



### Head Position

The tops of your child's ears **MUST be below** the top of the car seat.


5



### Harness Strap Position

The harness strap **MUST** be **at or slightly above** the shoulders; never below.

6



### Buckle Position

- Use the slot closest to your child.
- The buckle **should not be underneath or behind** your child.

The buckle can be used in **any** buckle slot.

i

To change the harness strap height, see pages 33-35.

To change the buckle position, see page 36-38.

To learn how to check harness tightness, see pages 30-32.

If you cannot achieve a snug harness fit for your child, see pages 39-44.

## Forward-Facing Vehicle Install

23



Before installing the car seat in your vehicle, check to see if you need to adjust the buckle position or harness height for your child. **See page 21 for child fit.**

Once the car seat is installed, you will not be able to adjust the buckle position or the harness strap height.

### Review Vehicle Owner's Manual

Determine what kind of vehicle belts your car has and how to use them to lock a car seat in place **OR** where LATCH: lower anchor seating positions are located in your vehicle.

There are 2 different methods for install.

**Use only one:**



**Vehicle Belt**

**OR**




**LATCH: Lower Anchor Belt**

## **⚠ WARNING:**

**DO NOT** use both the LATCH: lower anchor belt and vehicle belt at the same time to install the car seat.

You **MUST ALWAYS** attach, adjust, and secure the tether (top anchorage) strap when installing the car seat in the Forward-Facing Mode with internal harness.


1



### **Place Car Seat Forward-Facing in Back Seat**

The vehicle seat back **MUST** be upright.

i



If your vehicle has a headrest that interferes with a flush car seat fit, check your vehicle owner's manual to see if it can be removed, adjusted, or if there are other possible seating locations for you to install.

*continued on next page*


2



### Locate Vehicle Top Tether Anchors


Review your vehicle owner's manual for top tether anchor locations and how to route the tether strap when there are vehicle headrests.

3




### Lift Tether Adjuster to Loosen Tether Strap

4



### Loosely Attach Tether Hook to Vehicle's Top Tether Anchor

5



## Locate **Forward-Facing Belt Path** & Route Vehicle Belt or Lower Anchor Belt Through It

**For the LATCH belt:** You may need to fully lengthen the belt before routing it into the belt path. Squeeze the adjuster button and pull the belt out as shown.




Connector



Hook


6



## Vehicle Belt or Lower Anchor Belt Goes:

- under the car seat pad; **AND**
  - across the car seat; **AND**
  - out the other **Forward-Facing Belt Path** opening.
- DO NOT twist the belt.**


i




## Finished Lower Anchor Belt Routing

*continued on next page*

7



OR




**Depending on Your Model:  
Attach Lower Anchor Belt Connectors  
or Hooks to Vehicle's Lower Anchors  
As Shown**

### **Buckle Vehicle Belt**

If your car has a **switchable retractor**, use it to lock the vehicle belt. Review page 55 of this manual or your vehicle owner's manual.


i



The lower anchor connector should be attached to the vehicle's lower anchor bar with the thicker side at the top as shown.

**DO NOT** twist the belt.


8




### Tighten Belt

Place your hand in the car seat and firmly push the car seat down and back towards the vehicle seat. Pull the belt towards you and parallel (in line) with the belt path as shown.

**For the LATCH belt or Lap Only Vehicle Belt:** it may be easier to tighten if you route the free end of the belt back into the **Forward-Facing Belt Path**, reach into the **Forward-Facing Belt Path**, and pull the free end of the belt towards you.




9



### Tighten Tether

Push firmly on the back of the car seat and pull the free end of the tether strap to remove all of the slack.

10



### Check Belt Tightness

Hold the **Forward-Facing Belt Path** with your non-dominant hand. Push and pull from side to side. The car seat should not move more than **1 in.** (2.5 cm).

i

If the car seat moves more than **1 in.** (2.5 cm), you can try:

- Pulling the belt tighter; **OR**
- Reinstalling the car seat; **OR**
- Changing to a different seating location; **OR**
- Switching to a different install method (LATCH or vehicle belt).

*continued on next page*

## FINISHED!



**Lap/Shoulder Belt + Tether**



**Lap Belt + Tether**




**LATCH: Lower Anchor Belt + Tether**



- Vehicle Belt Install:** Is the vehicle belt locked? See step 7.
- LATCH: Lower Anchor Belt Install:** Are the connectors or hooks securely attached to the vehicle's lower anchors? See step 7.
- Is the belt tightened enough so the car seat does not move more than 1 in. (2.5 cm) from side to side? Check the tightness of the install often to make sure it has not loosened. See steps 8 and 10.
- Has the tether been installed and tightened? See steps 4 and 9.

## Securing Child in Car Seat


1



### Place Child in Car Seat

Your child's bottom and back should be flat against the car seat.


2



### Buckle Harness

Pull the harness straps up to make sure the buckle is locked.


3



### Fasten Chest Clip

Insert right half of the chest clip into the left half and snap together.

4




### Tighten Harness

Pull the harness adjustment strap straight out to snugly tighten the harness.

*continued on next page*


5



### Position Chest Clip

Slide the chest clip up the harness straps and position it at mid-chest (even with armpits) and away from your child's neck.

6



### Check Harness Tightness

Unfasten the harness covers.

Try to pinch the harness at the shoulders vertically between index finger and thumb as shown.

**If your fingers slip off**, the harness is tight enough.

**If you can pinch the harness strap**, tighten more.

Fasten the harness covers.

i

A snug strap should not allow any slack.

It lies in a relatively straight line without sagging.

It does not press on the child's flesh or push the child's body into an unnatural position.

## FINISHED!



Your child is now secured in the car seat. Check your child's fit often and make any needed adjustments to the car seat as they grow.

- To Remove Child from Car Seat:** Clean with warm water and/or remove the object with tweezers. If you cannot get the harness to adjust and remain tight with the buckle securely locked, **DO NOT** use this car seat.
1. Loosen Harness Strap
  2. Unbuckle Harness
  3. Release Chest Clip
  4. Remove Child

### Troubleshooting

1. **If the buckle or harness release lever sticks: DO NOT lubricate.** Check for dropped food, sticky spilled drinks, dirt, leaves, etc.
2. **If your harness twists:** Straighten the harness each time you put your child in the car seat. Lock the buckle and tighten the harness so it will be ready for next use.

## ⚠️ WARNING:

Failure to fasten and tighten the harness system correctly may allow the child to be ejected from the child restraint in a crash or sudden stop causing serious injury or death.

**DO NOT** mistake comfort for safety. The harness system must be snugly adjusted.




**DO NOT** put snowsuits or bulky garments on your child when placing them in the child restraint.

Bulky clothing can prevent the harness straps from being tightened properly.

## Changing Harness Height

33


1



### Fully Loosen Harness Straps

Push down on the harness release lever (through the opening in the pad) while pulling out on the harness straps as shown.

2




### From Back of Car Seat, Remove Harness Straps Loops From Splitter Plate

### **WARNING:**


The harness system **MUST** be installed correctly. **DO NOT** use a child restraint with damaged harness straps.

3



**Pull Harness Straps  
Out of Shoulder  
Harness Slots**

4



**Rethread Harness  
Straps into Correct  
Shoulder Harness Slots  
For Your Child**


i

**For Rear-Facing Child  
Fit**, see page 9.

**For Forward-Facing  
Child Fit**, see page 21.


*continued on next page*

5



**Attach Harness  
Strap Loops to  
Splitter Plate**

i



The sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist the harness strap or the harness adjustment strap.

Make sure the harness strap loops are fitted completely on both sides of the splitter plate.

To learn how to check harness tightness, see pages 30-32.

If you cannot achieve a snug harness fit for your child, see pages 39-44.

**Check the harness straps often for any wear or damage.**

## Changing Buckle Position


1



### Unbuckle Harness

It may be easier to undo the buckle by pressing in towards the top of the button.

2



### Turn Car Seat Over


Locate the buckle's metal retainer on the bottom of the car seat.

## WARNING:

Failure to place buckle's metal retainer completely through pad and child restraint can result in serious injury or death.

*continued on next page*

3




Rotate Metal Retainer & Push It Up Through Buckle Slot in Car Seat

4



From Top of Car Seat, Pull Buckle Out of Car Seat & Pad

5



Insert Buckle's Metal Retainer into Slot Closest to Child


The buckle **MUST** face out.

i

For Rear-Facing Child Fit, see page 9.

For Forward-Facing Child Fit, see page 21.

6



**Pull Buckle's Metal Retainer Completely Through Pad & Car Seat**

7



### **Check Buckle**

Pull the buckle up to make sure it is secured.

The buckle **MUST NOT** pull out.

**i**

To learn how to check harness tightness, see pages 30-32.

If you cannot achieve a snug harness fit for your child, see pages 39-44.

**i**


If you cannot achieve a snug harness fit for your child, you may need to adjust the buckle strap and/or harness strap length as shown in this section.

### **! WARNING:**

The harness system **MUST BE** installed correctly. **DO NOT** use a child restraint with damaged harness straps.


### Adjusting Buckle

1



**Pull Front of  
Car Seat Pad Up**


2



**With Buckle in 1st Slot As  
Shown, Turn Car Seat Over**


If you need to move the buckle to the 1st slot, see pages 36-38.

3



From Bottom of Car Seat,  
Pull Metal Retainer Towards  
You & Push It Up into Middle  
Slot As Shown

4



From Top of Car Seat,  
Lay Metal Retainer  
Flat Against Car Seat  
As Shown

5




**Check Buckle**

Pull the buckle up to make sure it  
is secured. The buckle **MUST NOT**  
pull out.

*continued on next page*


## Adjusting Harness Straps

1


**Fully Loosen  
Harness Straps**

Push down on the harness release lever (through the opening in the pad) while pulling out on the harness straps as shown.


2

**From Back of Car Seat,  
Remove Harness Strap  
Loops From Splitter Plate**

3


**Pull Harness Straps  
Out of Shoulder  
Harness Slots**

4

**Unthread Chest Clip  
& Buckle**


**DO NOT** undo the buckle.

5




Lift Up Front of Car Seat Pad & Turn Car Seat Over

6



Pull Harness Strap Down & Out of Hip Harness Slot


7



Weave Harness Strap In & Out of Car Seat

*continued on next page*


8



**From Top of Car Seat,  
Thread Harness Strap  
Up Through Slot in  
Seat Pad**

The harness strap goes behind the buckle strap. Replace the seat pad around the front of the car seat.


9



**Make Harness  
Strap Even**

The sewn ends of the harness strap loops **MUST** face each other.


10



**Thread Buckle &  
Chest Clip**

The harness strap end goes through the **back** of the buckle tongues and through the chest clip **front to back** as shown.

11




**Thread Harness  
Strap Into Correct  
Shoulder Harness  
Slots for Your Child**

i

For Rear-Facing Child Fit, see page 9.


For Forward-Facing Child Fit, see page 21.

12



### Attach Harness Strap Loops to Splitter Plate

i



The sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist the harness strap or the harness adjustment strap.

Make sure the harness strap loops are fitted completely on both sides of the splitter plate.

To return the harness strap to its original configuration:

1. Go to page 45 and follow steps 1-6.
2. Then go to page 48 and follow steps 2-7.

## Removing Seat Pad & Harness System


45

**i**

Only remove the harness system to clean the seat pad.

To remove accessories, see pages 3-4.

1



### Fully Loosen Harness Straps


Push down on the harness release lever (through the opening in the pad) while pulling out on the harness straps as shown.

2




### From Back of Car Seat, Remove Harness Straps Loops From Splitter Plate

3




### Pull Harness Straps Out of Shoulder Harness Slots

4




**Unthread Chest Clip**

5




**Unthread Buckle**  
DO NOT undo the buckle.

6



**Pull Harness Strap  
Out of Car Seat**

7



**Pull Pad Off  
of Car Seat**

## Cleaning Parts of Car Seat

47

### Cleaning Pad & Accessories

Machine wash separately with cold water on a gentle cycle. On select models: Make sure the harness covers are closed so the fastening strips are not exposed. **DO NOT** use bleach. Tumble dry separately for 10-12 minutes on low heat. Remove immediately.

### Cup Holder

The cup holder is top-rack dishwasher safe.

### Cleaning Harness Strap

**Check the harness straps often for any wear or damage.** Spot clean using warm sudsy water and damp cloth. Spilled food and liquids on the car seat may result in mold or bacterial growth over time. These spills could also attract insects or rodents.

### Cleaning Buckle & Car Seat


Spot clean using warm sudsy water and damp cloth. **DO NOT** submerge into water.

## WARNING:

**DO NOT** use the child restraint without the seat pad or with damaged harness straps.

## Installing Seat Pad & Harness System


1



### Starting from Bottom of Car Seat, Slip Pad on Car Seat

Pull the harness adjustment strap and the buckle through the slots in the pad.


2



### Thread Harness Strap

With the sewn end of harness strap loop facing the buckle, thread the harness strap down through the hip harness slot.

3




### Pull Harness Strap Across Bottom of Car Seat

The harness strap **MUST** lie in front of the harness adjustment strap as shown. Push the harness strap up through the other hip harness slot.

*continued on next page*


4



### Make Harness Strap Even

The sewn ends of the harness strap loops **MUST** face each other.


5



### Thread Buckle & Chest Clip

The harness strap end goes through the **back** of the buckle tongues and through the chest clip **front to back** as shown.

6




### Thread Harness Straps Into Correct Shoulder Harness Slots For Your Child

i

For Rear-Facing Child Fit, see page 9.

For Forward-Facing Child Fit, see page 21.

7



Attach Harness Strap Loops to Splitter Plate

i




The sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist the harness strap or the harness adjustment strap.

Make sure the harness strap loops are fitted completely on both sides of the splitter plate.


# LATCH: Lower Anchor Belt

51




Your vehicle's features may be considerably different than those pictured here.

The lower anchors of **LATCH** (**L**ower **A**nchors and **T**ethers for **C**hildren) is a universal system for installing car seats without using vehicle seat belts. The LATCH: lower anchor belt can **ONLY** be used in vehicles that have the lower anchor bars installed in designated seating positions. Most vehicles manufactured after September 2002 are equipped with LATCH: lower anchor bars. Check your vehicle owner's manual to see which seating positions may be equipped with LATCH: lower anchor bars.



**Lower Anchor Belt Storage Location**



**Lower Anchor Belt Parts Style Depends on Model**

## To Remove Lower Anchor Belt from Storage Location on Car Seat

**For Lower Anchor Connectors:** Press the red release button on each connector and remove connectors from the storage attachments.

**For Lower Anchor Hooks:** Squeeze the spring lever on the hooks and remove the hooks from the storage attachments.



Connectors




Hooks

### To Remove Lower Anchor Belt from Vehicle's Lower Anchor Bars

**For Lower Anchor Connectors:** Press the red release button on each connector, then pull the connectors out of the vehicle seat.

**For Lower Anchor Hooks:** Remove the tension from the belt by pushing down on the side of the car seat with the adjuster. Then press the adjuster's button to loosen the belt.

Remove the hook from the anchor by squeezing the spring lever on the hook, pushing the hook back into the seat bight, and rotating the hook to the side. Then pull the hook out of the vehicle seat bight.



### To Store Lower Anchor Belt

The lower anchor belt **MUST** be properly stored in its storage location when:

- using the vehicle belts to install the car seat; **OR**
- the car seat is not installed in a vehicle.

**When installing Rear-Facing with vehicle belt,** thread the lower anchor belt through the **Forward-Facing Belt Path** as shown.


**When installing Forward-Facing with vehicle belt,** thread the lower anchor belt through the **Rear-Facing Belt Path**.

Then attach connectors or hooks to storage attachments near the **Rear-Facing Belt Path** as shown.

Gently pull the free end of the belt to remove slack.

## **⚠ WARNING:**

**DO NOT** use both the lower anchor belt and vehicle belt at the same time.




Your vehicle's features may be considerably different than those pictured here.

If LATCH: lower anchors are not an option, you must use the vehicle seat belt system to install the car seat.

**Not all vehicle belts and seating positions will work with car seats. Please go through the following steps to understand how to lock a car seat in [Rear-Facing Mode](#) or [Forward-Facing Mode](#) with a vehicle belt.**

1



## You MUST Review Your Vehicle Owner's Manual

Your vehicle owner's manual will let you know which vehicle belts and seating positions car seats can be installed in.

2



### Check How This Car Seat Will Be Locked Into Place


The vehicle belt **MUST NOT** loosen after tightening.

This means there needs to be a way to lock the vehicle belt.

The ways this can be done are:

- By using the seat belt's retractor (see step 3); **OR**
- By using the seat belt's latch plate (see step 4).

3



### Check Retractor

Retractors pull seat belts into stored positions and lock the belt to hold passengers in place.

See the next page for some common types of vehicle belt retractors that will work with this car seat.

*continued on next page*

## Types of Retractors



### Switchable Retractor

(most vehicles have this type)

This retractor can be switched to a locking mode.

You **MUST have the retractor in the locking mode** to use the seat belt with this car seat.

**Switching to locking mode:** Slowly pull the shoulder belt all the way out, then let it go back in **1-2 in.** (2.5-5 cm).

As it goes back in, you will most likely hear a ratcheting sound.

Gently pull the belt to see if it has locked. You will not be able to pull any more belt out if the lock has engaged.



### Automatic Locking Retractor

This retractor always locks.

It will automatically lock after slowly pulling the seat belt out at least halfway and letting the belt go back into the retractor **1-2 in.** (2.5-5 cm).




### Emergency Locking Retractor

#### See Step 4 “Check Latch Plates”


If the retractor does not lock, it is most likely an Emergency Locking Retractor. These retractors only lock during a sudden stop or collision.

You will need to determine if your seat belt's latch plate can lock the belt. See step 4, “Check the Latch Plates”.

4



Locking  
Latch Plate



Emergency  
Locking  
Retractor with  
a Sliding Latch  
Plate

## Check Latch Plates

Latch plates are the part of the seat belt that goes into the buckle.

**To see if the latch plate locks:**

1. Buckle Vehicle Belt
2. Firmly Tug Lap Portion of Seat Belt While Pulling It Up

If the vehicle belt does not slide through the latch plate, it's locked.

If the latch plate slides up and down the vehicle belt, it is a **sliding latch plate**.

Sliding latch plates easily slip between the lap and shoulder portions of the belt.

i

If you have an Emergency Locking Retractor with a Sliding Latch Plate, you must use a locking clip.


Please contact us for one, see the back cover of the manual or page 66.

**Never Use the Following With This Car Seat:**

- Emergency Locking Retractor Lap Only Belt
- Inflatable Seat Belts

## Top Tether

57




Your vehicle's features may be considerably different than those pictured here.

You **MUST** always attach, adjust, and secure the tether (top anchorage) strap when installing the car seat in the **Forward-Facing Mode** with internal harness. Tethers improve the installation and stability of car seats and reduce the risk of injury. Attach the tether hook to the tether anchor designated by your vehicle manufacturer for that seating position. Check your vehicle owner's manual for more information. If the seating position does not have a tether anchor, use a different seating position or see your dealer or a qualified mechanic and have one installed.

### **! WARNING:**

Using this child restraint without the tether strap anchored as required by the manufacturer would be a misuse of the child restraint and, in a sudden stop or crash, could result in serious injury or death.

**DO NOT** fasten multiple tether hooks on the same tether anchor in the vehicle.



### Storing Top Tether Strap

The tether strap **MUST** be properly stored in its storage location when:

- installing in **Rear-Facing Mode**; **OR**
- the car seat is not installed in a vehicle.

Attach the tether hook to its storage location as shown. Gently tighten to remove slack.

## Child Restraint Use

### **WARNING:**

**NEVER** take your child out of the child restraint while the vehicle is moving.

**NEVER** leave your child unattended. Placing your child in a hot child restraint may result in burns.

**DO NOT** use a child restraint with damaged or missing parts.

**DO NOT** use a child restraint with cut, frayed, or damaged harnesses.

**DO NOT** substitute parts or try to modify the child restraint in any way. **DO NOT** lubricate buckles and fasteners.

**DO NOT** use any child restraint accessory except those approved by Dorel Juvenile Group.

**NEVER** allow any child to play with this child restraint; it is not a toy.

**DO NOT** remove or cover up any of the warning labels or other labels on the child restraint.

This child restraint has been certified for use in passenger vehicles. **DO NOT** use in a boat, on a motorcycle or in a cargo van or bus where there are no seat belts or tether anchors.

Read all instructions for additional warnings.

### **WARNING:**



**NEVER** place a child rear-facing in a seating position with an active frontal air bag.

Check the vehicle owner's manual for more information about air bag/child restraint use.



Use the child restraint only on vehicle seats that face forward.



**DO NOT** use on seats that face the sides or rear of the vehicle.

For vehicles without a back seat, refer to your vehicle owner's manual.



Children are safer when properly restrained in rear seating positions than in the front seating positions.

**According to accident statistics, children in rear seating positions are statistically safer, whether you have air bags, advanced air bags, or no air bags at all.**

**If you are not sure where to place the car seat in your vehicle:**

- Consult your vehicle owner's manual; **OR**
- Contact Dorel Juvenile Group Consumer Care Department; **OR**
- Visit your local Child Passenger Inspection Station. Go to <https://www.nhtsa.gov/equipment/car-seats-and-booster-seats> to find your closest station.

## Installation in Vehicle

To avoid your child being seriously burned, take the following precautions:

- Park in the shade or where the sun does not directly hit the car seat.
- Cover the car seat with a sheet or blanket when not in use.
- Check for hot seat and buckles before placing child in car seat.

To help protect your vehicle seat's upholstery from damage: you may use an accessory approved by Dorel Juvenile Group or a single layer towel underneath and behind car seat.

### WARNING:

Check the vehicle belt or lower anchor belt before each use. Use only if the belt can be tightened properly and locked securely in place.

Even when unoccupied, this child restraint **MUST** be firmly secured to the vehicle with the lower anchor belt or with the vehicle seat belt.

In a crash or sudden stop, an unsecured child restraint could injure occupants.

## DO NOT risk your child's safety.

To keep your child as safe as possible, Dorel Juvenile Group strongly recommends replacing the car seat even after a minor crash; even if it was not occupied at the time.

### Replacement After a Minor Crash

The National Highway Traffic Safety Administration states that for a crash to be considered minor **ALL of the following MUST be true:**

- Vehicle able to drive away from the crash site; **AND**
- Vehicle door nearest the car seat was not damaged; **AND**
- No passengers were injured; **AND**
- Airbags did not deploy; **AND**
- There is no visible damage to the car seat.

If the crash your car seat was involved in meets **ALL** the

criteria, you may not need to replace the car seat. If one or more of these criteria are not true or if you are uncertain of any of your answers, replace the car seat immediately.

### Replacement After a Moderate to Severe Crash

You **MUST** replace this car seat if it has been in a moderate to severe car crash.

This car seat is intended to protect a child in a single crash. During a crash, the car seat and all of its parts absorb crash energy which can deform or weaken it. Damage is not always visible. A damaged car seat **MUST** be replaced immediately.



### Expiration

On the side of the car seat there is a date of manufacture label as shown.

**DO NOT** use this car seat more than 8 years after the date of manufacture.

## Registration & Safety Notices

Please complete the postage-paid registration card that came with your child restraint, and send it to us.

Child restraints could be recalled for safety reasons.

You must register this restraint to be reached in a recall.

Send your name, address, e-mail address if available and the restraint's model number and manufacturing date to:

### Dorel Juvenile Group

2525 State Street  
Columbus, IN 47201

or call 1-800-951-4113 or register online at <https://www.maxicosi.com/us-en/registration/>.

For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY: 1-800-424-9153), or go to [www.NHTSA.gov](http://www.NHTSA.gov).

Model Number	Model Name	Manufacture Date
AB123CDE	Maxi-Cosi Car Seat	05/16/2015

Example of model number, manufacture date, and line code.



If you don't have the card or if your address changes, you will find the model number, manufacture date, and line code on the label located on the side of the car seat.

This restraint is certified for aircraft use.



## Rear-Facing Aircraft Installation

Follow the steps on pages 11-17.




## Forward-Facing Aircraft Installation

Follow the steps on pages 23-28, skipping the tether strap steps.

Install the car seat in a window seat to avoid blocking the aisle. If the aircraft lap belt is too short, ask the flight attendant for a belt extender.

Use only on forward-facing aircraft seats. Contact the airline for their specific policies.



Some airlines may ask to see a label stating that this car seat is certified for aircraft use.

There is an airplane certification label located on the side of this car seat as shown.

## **WARNING:**

You **MUST** store the lower anchor belt and tether strap when installing with aircraft belts.

## Warranty

Dorel Juvenile Group, Inc. (DJG) warrants this product to the original retail purchaser as follows: This product is warranted against defective materials or workmanship for one year from the date of original purchase.

### **An original receipt is required to validate your warranty.**

DJG will, at its option, provide replacement parts or replace this product. DJG reserves the right to substitute if the part or model has been discontinued.

To make a claim under this warranty, please contact our Consumer Care Department by phone: 1-800-951-4113 or text: 1-812-652-2525. Our hours of operation are from 8:00 a.m. to 6:00 p.m. EST Monday through Thursday and from 8:00 a.m. to 4:30 p.m. on Friday.

**Proof of purchase is required and shipping charges are the responsibility of the consumer.**

**Warranty Limitations:** This warranty does not include damages which arise from misuse or abuse of this product.

**Limitation of Damages:** The warranty and remedies as set forth are exclusive and in lieu of all others, oral or written, expressed or implied. In no event will DJG or the dealer selling this product be liable to you for any damages, including incidental or consequential damages, arising out of the use or inability to use this product.

**Limitation of warranties and other warranty terms and state law rights:** Any implied warranties, including implied warranties of the merchantability and fitness for a particular purpose, shall be limited to the duration and terms of the express written warranty.

Some states do not allow limitations as to how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Neither DJG nor the dealer selling this product authorized any person to create for it any other warranty, obligation, or liability in connection with this product.

**Please note:** Our product warranty only applies when purchased from an authorized Maxi-Cosi retailer. The origin of products not purchased through these authorized retailers is unknown and could be counterfeit.

We cannot support products from an unknown origin as we cannot verify the handling or condition of such merchandise. We maintain a strong network of authorized retailers to ensure you are purchasing safe and complete products.

Fulfillment by a third party does not guarantee you are purchasing from one of these authorized retailers. Pricing which is inconsistent with the majority of retailers is a strong indication that the retailer is not authorized, as we have a consistent price offering across all authorized retailers.

If you are unsure of the authorization status of a retailer you are considering purchasing from, or have purchased from, you can check [www.maxicosi.com/us-en/find-a-retailer](http://www.maxicosi.com/us-en/find-a-retailer); or call our Consumer Care Department at 1-800-951-4113; or text us at 1-812-652-2525.

## Replacement Parts List

(on select models)

- Buckle Assembly
- Chest Clip
- Harness Strap
- Seat Pad Set
- Removable Cup Holder
- Lower Anchor Belt
- Top Tether
- Locking Clip
- Instructions

**For parts availability and questions, call, text, or chat.**

**If requested color is not available, similar color will be substituted.**

**Applicable tax and shipping & handling will also be added.**



### Send Us a Text:

1-812-652-2525

(US and Canada Only  
Carrier Fees May Apply)



### Find Us Online:

[www.maxicosi.com](http://www.maxicosi.com)

### Email Us:

[support@djgusa.com](mailto:support@djgusa.com)



### Give Us a Call:

1-800-951-4113

(Toll Free  
US and Canada Only)



**Send Us a Text:** 1-812-652-2525  
(US and Canada Only. Carrier Fees May Apply)



**Find Us Online:** [www.maxicosi.com](http://www.maxicosi.com)  
**Email Us:** [support@djgusa.com](mailto:support@djgusa.com)



**Give Us a Call:** 1-800-951-4113  
(Toll Free, US and Canada Only)